



The Most Moisture Resistant OSB GP Produces

Maximum Protection From the Elements

DryMax™ OSB sub-floor has exceptionally low thickness swell when exposed to moisture, helping to avoid costly and time-consuming joint sanding. Plus it has an enhanced clear edge seal to help reduce edge swell.

Strong. Smooth. Fast.

These panels have enhanced nail holding ability, stiffness and strength, plus there are no core voids, knots or splits. DryMax OSB is sanded on two sides for top and bottom surface smoothness and consistency. And it has printed fastener guidelines for ease and speed of installation.



300 Day No-Sand Guarantee

DryMax is backed by a 300 day no-sand guarantee* that covers the edges of the panels. Plus it carries a lifetime limited warranty. That's peace of mind for both you and your customers.

* See warranty for complete details available at www.gp.com/build or by calling 800-284-5347.



What You Don't See Matters.™
Build It Better.®



DRYMAX, WHAT YOU DON'T SEE MATTERS, BUILD IT BETTER and the DryMax and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. The NAHB Research Center Green Approved logo is a trademark of the NAHB Research Center. The FSC logo is a trademark of Forest Stewardship Council. © 2010 Georgia-Pacific Wood Products LLC. All rights reserved. 8/10. Lit. Item # 621510



For installation instructions, specifications and warranty, please visit www.gp.com/build

800-284-5347